

Diesel Recovery

Emergency Fuel Treatment for Gelled Diesel Fuel

AMSOIL Diesel Recovery (DRC) is an emergency diesel fuel treatment that dissolves the wax crystals that form when diesel fuel has surpassed its cloud point. Diesel Recovery liquefies gelled diesel fuel and thaws frozen fuel filters, avoiding costly towing charges and getting diesels back on the road.

For preventive maintenance, use Diesel Cold Flow (ADD) or Diesel All-In-One (ADB).

Fast Fuel Recovery

Diesel applications operating in extremely cold environments face some unique challenges. As the temperature drops, wax naturally found in diesel fuel begins to form crystals. The point at which wax crystals form is known as the cloud point. These wax crystals can eventually clog the fuel filter and starve the engine of fuel, preventing it from starting or even stalling out a running engine.

Diesel Recovery quickly dissolves gelled fuel to allow the operator to continue driving with minimal downtime. Diesel Recovery separates the molecular bonds of wax crystals that have agglomerated in diesel fuel. It thaws frozen fuel filters and reduces the need for a new filter, saving money and preventing an inconvenient trip to an auto parts store.

Works Well in Many Diesel Blends

The marketplace offers many different diesel fuels, all with varying quality. Diesel Recovery performs well in all diesel fuels, including ULSD, off-road and biodiesel.

Non-Corrosive, Alcohol-Free Formulation

Over extended use, alcohol has a tendency to degrade components of some fuel delivery systems. Diesel Recovery contains no alcohol, making it safe for repeated treatments. In addition, Diesel Recovery is non-corrosive and contains no chemicals that interact with fuel system components. Corrosion can damage fuel system components and lead to prematurely-clogged fuel filters.

Safety in a Bottle

Diesel fuel quality varies from one filling station to the next, and low-quality fuel can have a cloud point as high as 40°F. Keeping a bottle of Diesel Recovery on-board is cheap insurance against being towed to a service station or getting stranded somewhere in subzero temperatures.

PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit AMSOIL.com/warranty.aspx.

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use.



- Quickly dissolves gelled fuel.
- Thaws frozen fuel filters.
- **Performs** well in ULSD, off-road & biodiesel.
- Alcohol-free.
- Non-corrosive.

RECOMMENDATIONS

One 30 oz. bottle of Diesel Recovery treats up to 30 gallons of fuel. When encountering a gelled fuel system, follow these steps for maximum effectiveness:

- 1. Remove existing fuel filter.
- 2. Fill fuel filter with Diesel Recovery.
- 3. Reinstall fuel filter.
- Add remaining Diesel Recovery to fuel tank. If necessary, add more as required by treat rate recommendations.
- 5. Start engine and allow fuel system to circulate until full power has been restored. Note: For even quicker restoration of power, install new fuel filter instead of using existing filter.

AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.



Jeff Fisher 866-292-4700 www.SyntheticOils.us

DATA SHEET