



Fisher Resource Solutions

AMSOIL Maintains Drain Interval Recommendations for Premium Diesel Oils

AMSOIL Premium Diesel Oils have shown the ability to maintain integrity in the face of fuel dilution in 2007-2009 light-duty diesel applications and continue to be recommended for three times the vehicle manufacturer recommendation, not to exceed 50,000 miles/600 hours or one year. However, it is recommended that owners of 2007-2009 Dodge, Ford and GM light-duty diesel vehicles perform regular oil analysis as a precautionary measure. If oil analysis reveals greater than 5% fuel dilution, AMSOIL recommends changing the oil. The company will continue to closely monitor this situation, and if deemed necessary, will adjust recommended drain intervals in these applications.

New Simplified Diesel Oil Drain Recommendations

In order to simplify recommendations and streamline business for Dealers, AMSOIL Series 3000 Synthetic 5W-30 Heavy Duty Diesel Oil (HDD), Synthetic 15W-40 Heavy Duty Diesel and Marine Oil (AME) and Synthetic 10W-30/SAE 30 Heavy Duty Diesel Oil (ACD) now carry a three times the OEM recommendation similar to the recommendation for AMSOIL Premium Diesel Oils. The AMSOIL Product Recommendation and Drain Interval Guide (G1490) and all relevant data bulletins are being revised to reflect these changes.

	All Pre-2007 Applications	2007-Present Personal Light Truck Vehicles with Diesel-Fueled Engines	2007-Present Heavy-duty On/Off-Road Applications, Fleet, Marine and Motor Homes with Diesel Engines
DEO DME	3X OEM recommendations, not to exceed 50,000 miles/ 600 hours or one year.	3X OEM recommendations, not to exceed 50,000 miles/600 hours or one year.	3X OEM recommendations, not to exceed 50,000 miles/600 hours or one year.*
HDD AME ACD	3X OEM recommendations, not to exceed 50,000 miles/	-. -. .-	-. -. .-

*Except in 2007-present Cat C13 and C15 applications. In those applications, follow OEM recommendations.